

Distributed by:



www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached
material are the property of its owner.

Overall Beldfoil® Shield

Audio, Control and Instrumentation Cables
Non-Plenum


Jameco Part Number 233251
(8771-060-1000)

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance			
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m


22 AWG Stranded (7x30) • Tinned Copper • Conductors Cabled • Overall 100% Beldfoil Shield • 22 AWG Stranded TC Drain Wire

Polypropylene Insulation • Brown PVC Jacket

300V RMS	9770	NEC: CM	3	Black, Red, White	U-500 500 U-1000 1000	U-152.4 152.4 U-304.8 304.8	9.0 9.0 17.0 17.0	4.1 4.1 7.7 7.7	.008 .20	.020	.51	.145	3.68	32	105	60	197
----------	-------------	------------	---	-------------------------	--------------------------------	--------------------------------------	----------------------------	--------------------------	-------------	------	-----	------	------	----	-----	----	-----

**Polyethylene Insulation • Chrome PVC Jacket**


UL AWM Style 2093 (300V 60°C)	8771	NEC: CM	3	Black, Red, Clear	250 500 U-1000 1000 10000	76.2 152.4 U-304.8 304.8 3048.0	6.3 12.0 24.0 24.0 240.0	2.8 5.5 10.9 10.9 109.1	.016 .41	.033	.84	.199	5.05	23	75	41	134
----------------------------------	-------------	------------	---	-------------------------	---------------------------------------	---	--------------------------------------	-------------------------------------	-------------	------	-----	------	------	----	----	----	-----



22 AWG Stranded (19x34) • Tinned Copper • Conductors Cabled • Overall 100% Beldfoil Shield • 23 and 25 AWG Drain Wires†

Polyethylene Insulation • White PVC Jacket

UL AWM Style 2094 (300V 75°C)	8729	NEC: CM, CL3	4	Black, Red, Green, Clear	U-500 500 U-1000 1000	U-152.4 152.4 U-304.8 304.8	23.5 23.5 46.0 47.0	10.7 10.7 20.9 21.4	.016 .41	.051	1.30	.257	6.53	22	72	42	138
----------------------------------	-------------	-----------------	---	-----------------------------------	--------------------------------	--------------------------------------	------------------------------	------------------------------	-------------	------	------	------	------	----	----	----	-----




† 8729 has three 23 AWG solid and one 25 AWG stranded tinned copper-coated steel drain wires.

20 AWG Stranded (7x28) • Tinned Copper • Conductors Cabled • Overall 100% Beldfoil Shield • 20 AWG Stranded TC Drain Wire

Polyethylene Insulation • Chrome PVC Jacket

UL AWM Style 2093 (300V 60°C)	8772	NEC: CM	3	Black, Red, Clear	U-500 500 U-1000 1000	U-152.4 152.4 U-304.8 304.8	16.0 16.0 31.0 31.0	7.3 7.3 14.1 14.1	.016 .41	.033	.84	.218	5.54	27	89	51	167
----------------------------------	-------------	------------	---	-------------------------	--------------------------------	--------------------------------------	------------------------------	----------------------------	-------------	------	-----	------	------	----	----	----	-----



TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to ground.

